



UNF Hexagon Head
Hi Tensile Bolt
SAE Grade 5 (8.8)
ANSI B.18.2.1.1996/BS 1768
Plain

d	1/4"-28	5/16"-24	3/8"-24	7/16"-20	1/2"-20	5/8"-18	3/4"-16	7/8"-14	1"-12
s	7/16	1/2	9/16	5/8	3/4	15/16	1.1/8	1.5/16	1.1/2
k	5/32	13/64	15/64	9/32	5/16	25/64	15/32	39/64	39/64
b < 6"	3/4	7/8	1	1.1/8	1.1/4	1.1/2	1.3/4	2	2.1/4
b > 6"	1	1.1/8	1.1/4	1.3/8	1.1/2	1.3/4	2	2.1/4	2.1/2

	1/4"-28	5/16"-24	3/8"-24	7/16"-20	1/2"-20	5/8"-18	3/4"-16	7/8"-14	1"-12
1									
1.1/4									
1.1/2									
1.3/4									
2									
2.1/4									
2.1/2									
2.3/4									
3									
3.1/4									
3.1/2									
3.3/4									
4									
4.1/2									
4.3/4									
5									
5.1/2									
6									
6.1/2									
7									
7.1/2									
8									
8.1/2									
9									
12									